



## The Future of LED Sports Lighting

# SportPro LED is the ultimate in LED sports floodlighting

Using critically controlled LED lighting arrays the SportPro LED floodlight produces optimum lighting levels whilst reducing light spillage and glare.

These floodlights are design for use in difficult lighting situations where dark skies compliance and light spillage must be kept to a minimum.

The SportPro LED floodlight uses soft start technology to reduce the switched load impact and increase component life.

A true retrofit LED floodlight to replace the old style HID metal halide lights.

The SportPro can offer a dimmable lighting solution to provide full match or practice lighting levels helping to further reduce running costs.

Long life and high reliability with a five year warranty as standard and an expected life of over 50,000hrs.



The SportPro LED uses multi-optic technology to fine tune the light distribution to provide optimum coverage.


- Energy savings of over 50% can be made when replacing HID floodlights.
- Ultracool system reduces the internal floodlight temperature increasing component life.
- All internal and external fixings are made from stainless steel
- With a High quality powder coat finish and an IP67 rating the SportPro LED floodlight is prepared for the harshest of environments.




Luminaire Data

Philips Lumileds 5050 LEDs  
 Colour temperature, 4000k or 5000k  
 Voltage, 90 - 305V (230v)  
 Net Weight ( 21kg - SP750AB )  
 Housing Colour, RAL6007  
 Luminaire Output, 260w - 750w  
 LED Lumen Output, >170lpw  
 CRI >70  
 High Power Factor >0.96  
 High Efficiency >0.95  
 IP67  
 Typical life expectancy, 50,000hrs

- Uses the latest multi optic technology.
- Ultra High Efficiency LED arrays.
- Temperature / surge & short circuit protected.
- 5 Year Warranty.
- High LED Lighting uniformity.
- Stainless Steel Fixings.
- Strong Corrosion Resistant Aluminium Housing.
- High Quality Powder Coat Finish.
- Dimmable 0v - 10v ( with additional cabling )
- Suitable upgrade for 1 & 2Kw HID floodlights.
- Supplied with a universal mounting bracket.




SIDE VIEW




REAR VIEW

Optional light spillage guard



Universal mounting bracket

SP750AB - 750w LED >115,200 lumen output, nw - 22.8Kg inc bracket  
 SP630AB - 630w LED > 96,000 lumen output, nw - 21.8Kg inc bracket  
 SP500AB - 500w LED > 76,800 lumen output, nw - 19.8Kg inc bracket  
 SP380AB - 380w LED > 57,600 lumen output, nw - 18.8Kg inc bracket  
 SP260AB - 260w LED > 38,400 lumen output, nw - 16.8Kg inc bracket



Polar Intensity Diagram  
 Asymmetric beam pattern